

JOINTS



EPDM O-RING

| Ø mm | | CODE |
|---------|----|----------|
| 15 | 10 | 9000N015 |
| 18 | 10 | 9000N018 |
| 22 | 10 | 9000N022 |
| 28 | 10 | 9000N028 |
| 35 | 10 | 9000N035 |
| 42 | 10 | 9000N042 |
| 54 | 10 | 9000N054 |
| 76,1 | 1 | 9000N076 |
| 88,9 | 1 | 9000N088 |
| 108 | 1 | 9000N0A0 |

FEATURES TECHNIQUES

Working temperature: -10° C to 110° C (120° C).
Diameter: Ø12 - Ø108 mm.

APPLICATIONS

- Drinking water.
- Deleble water.
- Rainwater.
- HEATING installations.
- Circulation pipes.
- Fire protection systems.



FPM O-RING (GREEN) - DIN ISO 1629

| Ø mm | | CODE |
|---------|----|----------|
| 15 | 10 | 9000V015 |
| 18 | 10 | 9000V018 |
| 22 | 10 | 9000V022 |
| 28 | 10 | 9000V028 |
| 35 | 10 | 9000V035 |
| 42 | 10 | 9000V042 |
| 54 | 10 | 9000V054 |
| 76,1 | 1 | 9000V076 |
| 88,9 | 1 | 9000V088 |
| 108 | 1 | 9000V0A0 |

TECHNICAL FEATURES

Working temperatura: -30° C to 160° C (200° C).
Diameter: Ø15 - Ø108 mm.

APPLICATIONS

- Air pressure systems.
- Steam and condensate installations.
- Solar installations.
- Refrigeration facilities.
- Hydrocarbons, except diesel.
- Mineral, vegetable and synthetic oil.



FPM O-RING (RED) - DIN ISO 1629

| Ø mm | | CODE |
|---------|----|----------|
| 15 | 10 | 9000R015 |
| 18 | 10 | 9000R018 |
| 22 | 10 | 9000R022 |
| 28 | 10 | 9000R028 |
| 35 | 10 | 9000R035 |
| 42 | 10 | 9000R042 |
| 54 | 10 | 9000R054 |
| 76,1 | 1 | 9000R076 |
| 88,9 | 1 | 9000R088 |
| 108 | 1 | 9000R0A0 |

TECHNICAL FEATURES

Working temperatura: -30° C to 160° C (200° C).
Diameter: Ø15 - Ø108 mm.

APPLICATIONS

- Air pressure systems.
- Mineral, vegetable and synthetic oil.
- Greases and industrial applications.
- Hydrocarbons, except heavy diesel.
- Liquefied petroleum gas (LPG).